

Safety data sheet

Page: 1/18

BASF Safety data sheet according to UN GHS 4th rev.

Date / Revised: 14.10.2020

Product: **N75-021 Hardener 2,5L**

Version: 2.3

(ID no. 50655498/SDS_GEN_00/EN)

Date of print 05.11.2020

1. Identification

Product identifier

N75-021 Hardener 2,5L

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: hardener

Recommended use: Sprayable

Details of the supplier of the safety data sheet

Company:

BASF Coatings GmbH

Postfach 6123

48136 Muenster

Deutschland

Telephone: +49/2501/143688

E-mail address: Product-Safety-Coatings@basf.com

Emergency telephone number

International emergency number:

Telephone: +49 180 2273-112

2. Hazards Identification

Classification of the substance or mixture

According to UN GHS criteria

Acute Tox. 5 (oral)

Skin Corr./Irrit. 3

BASF Safety data sheet according to UN GHS 4th rev.

Date / Revised: 14.10.2020

Version: 2.3

Product: **N75-021 Hardener 2,5L**

(ID no. 50655498/SDS_GEN_00/EN)

Date of print 05.11.2020

Eye Dam./Irrit. 2A
Skin Sens. 1
STOT SE 3 (Vapours may cause drowsiness and dizziness.)
STOT SE 3 (irritating to respiratory system)
Aquatic Acute 3
Flam. Liq. 3
STOT RE 2
Acute Tox. 5 (Inhalation - vapour)

For the classifications not written out in full in this section the full text can be found in section 16.

Label elements

Globally Harmonized System, UN (GHS)

Pictogram:



Signal Word:

Warning

Hazard Statement:

H226	Flammable liquid and vapour.
H303	May be harmful if swallowed.
H316	Causes mild skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H333	May be harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H402	Harmful to aquatic life.

Precautionary Statements (Prevention):

BASF Safety data sheet according to UN GHS 4th rev.

Date / Revised: 14.10.2020

Version: 2.3

Product: **N75-021 Hardener 2,5L**

(ID no. 50655498/SDS_GEN_00/EN)

Date of print 05.11.2020

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves, protective clothing and eye protection or face protection.
P264	Wash contaminated body parts thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P242	Use only non-sparking tools.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P243	Take action to prevent static discharges.
P233	Keep container tightly closed.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground and bond container and receiving equipment.
P260	Do not breathe dust or mist.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or physician if you feel unwell.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P370 + P378	In case of fire: Use water spray for extinction.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P333 + P313	If skin irritation or rash occurs: Get medical attention.
P303 + P361 + P353	IF ON SKIN (or hair): Remove or Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P304 + P312	IF INHALED: Call a POISON CENTER or physician if you feel unwell.
P337 + P313	If eye irritation persists: Get medical attention.
P314	Get medical advice/attention if you feel unwell.

Precautionary Statements (Storage):

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

Labeling of special preparations (GHS):

Repeated exposure may cause skin dryness or cracking. Contains isocyanates. May produce an allergic reaction.

Other hazards

According to UN GHS criteria

BASF Safety data sheet according to UN GHS 4th rev.

Date / Revised: 14.10.2020

Version: 2.3

Product: **N75-021 Hardener 2,5L**

(ID no. 50655498/SDS_GEN_00/EN)

Date of print 05.11.2020

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

3. Composition/Information on Ingredients

Substances

Not applicable

Mixtures

Chemical nature

polyisocyanate, organic solvent

Hazardous ingredients (GHS)

According to UN GHS criteria

Benzoic acid

Content (W/W): $\geq 1\%$ - $< 2\%$

CAS Number: 65-85-0

EC-Number: 200-618-2

Acute Tox. 5 (oral)

Acute Tox. 5 (dermal)

Skin Corr./Irrit. 2

Eye Dam./Irrit. 1

STOT RE (Lung) 1 (by inhalation)

H318, H315, H313, H303, H372

Ethylbenzene

Content (W/W): $\geq 1\%$ - $< 2\%$

CAS Number: 100-41-4

EC-Number: 202-849-4

INDEX-Number: 601-023-00-4

Asp. Tox. 1

Flam. Liq. 2

Acute Tox. 4 (Inhalation - vapour)

Acute Tox. 5 (oral)

STOT RE (Auditory organ) 2

Aquatic Acute 2

Aquatic Chronic 3

H225, H332, H303, H304, H373, H412, H401

4-Methylpentan-2-one

Content (W/W): $\geq 7\%$ - $< 10\%$

CAS Number: 108-10-1

EC-Number: 203-550-1

INDEX-Number: 606-004-00-4

Flam. Liq. 2

Acute Tox. 4 (Inhalation - vapour)

Eye Dam./Irrit. 2A

STOT SE 3 (irr. to respiratory syst.)

Acute Tox. 5 (oral)

Asp. Tox. 2

H225, H319, H332, H303, H305, H335

EUH066

BASF Safety data sheet according to UN GHS 4th rev.

Date / Revised: 14.10.2020

Version: 2.3

Product: **N75-021 Hardener 2,5L**

(ID no. 50655498/SDS_GEN_00/EN)

Date of print 05.11.2020

2-Butoxyethyl acetateContent (W/W): $\geq 7\%$ - $< 10\%$

CAS Number: 112-07-2

EC-Number: 203-933-3

INDEX-Number: 607-038-00-2

Flam. Liq. 4

Acute Tox. 4 (oral)

Acute Tox. 4 (dermal)

Aquatic Acute 3

H227, H302 + H312, H402

n-Butyl acetateContent (W/W): $\geq 20\%$ - $< 25\%$

CAS Number: 123-86-4

EC-Number: 204-658-1

INDEX-Number: 607-025-00-1

Flam. Liq. 3

STOT SE 3 (drowsiness and dizziness)

Aquatic Acute 3

H226, H336, H402

EUH066

Ethyl 3-ethoxypropionateContent (W/W): $\geq 7\%$ - $< 10\%$

CAS Number: 763-69-9

EC-Number: 212-112-9

Flam. Liq. 3

Acute Tox. 5 (oral)

Aquatic Acute 3

H226, H303, H402

Hexamethylene diisocyanateContent (W/W): $\geq 0,1\%$ - $< 0,2\%$

CAS Number: 822-06-0

EC-Number: 212-485-8

INDEX-Number: 615-011-00-1

Acute Tox. 4 (oral)

Acute Tox. 1 (Inhalation - mist)

Skin Corr./Irrit. 2

Eye Dam./Irrit. 2A

Resp. Sens. 1

Skin Sens. 1

STOT SE 3 (irr. to respiratory syst.)

H319, H315, H330, H302, H334, H317, H335

Specific concentration limit:Skin Sens. 1: $\geq 0,5\%$ Resp. Sens. 1: $\geq 0,5\%$ **Xylene**

BASF Safety data sheet according to UN GHS 4th rev.

Date / Revised: 14.10.2020

Version: 2.3

Product: **N75-021 Hardener 2,5L**

(ID no. 50655498/SDS_GEN_00/EN)

Date of print 05.11.2020

Content (W/W): $\geq 7\%$ - $< 10\%$	Asp. Tox. 1
CAS Number: 1330-20-7	Flam. Liq. 3
EC-Number: 215-535-7	Acute Tox. 5 (Inhalation - vapour)
INDEX-Number: 601-022-00-9	Acute Tox. 5 (oral)
	Skin Corr./Irrit. 2
	Eye Dam./Irrit. 2B
	STOT SE 3 (irr. to respiratory syst.)
	STOT RE (Central nervous system, Liver, Kidney) 2
	Aquatic Acute 2
	Aquatic Chronic 3
	H226, H320, H315, H333, H303, H304, H335, H373, H412, H401

p-Toluenesulphonyl isocyanate

Content (W/W): $\geq 0,3\%$ - $< 0,5\%$	Acute Tox. 5 (oral)
CAS Number: 4083-64-1	Skin Corr./Irrit. 2
EC-Number: 223-810-8	Eye Dam./Irrit. 2A
INDEX-Number: 615-012-00-7	Resp. Sens. 1
	STOT SE 3 (irr. to respiratory syst.)
	Aquatic Acute 3
	H319, H315, H303, H334, H335, H402
	EUH014
	EUH204

Specific concentration limit:

Skin Corr./Irrit. 2: $\geq 5\%$
 STOT SE 3, irr. to respiratory syst.: $\geq 5\%$
 Eye Dam./Irrit. 2: $\geq 5\%$

HDI-oligomer (trimer)

Content (W/W): $\geq 30\%$ - $< 50\%$	Acute Tox. 4 (Inhalation - dust)
CAS Number: 28182-81-2	Acute Tox. 4 (Inhalation - vapour)
EC-Number: 500-060-2	Skin Sens. 1
	STOT SE 3 (irr. to respiratory syst.)
	H332, H317, H335
	EUH204

For the classifications not written out in full in this section the full text can be found in section 16.

4. First-Aid Measures

Description of first aid measures

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove affected

BASF Safety data sheet according to UN GHS 4th rev.

Date / Revised: 14.10.2020

Version: 2.3

Product: **N75-021 Hardener 2,5L**

(ID no. 50655498/SDS_GEN_00/EN)

Date of print 05.11.2020

person from danger area. Immediately remove contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. If symptoms persist, seek medical advice. If breathing is irregular or stopped, administer artificial respiration.

On skin contact:

Flush with copious amounts of water for at least 15 minutes. Remove contaminated clothing immediately and clean before re-use or dispose it if necessary. Immediate medical attention required.

On contact with eyes:

Remove contact lenses, if present. Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Immediate medical attention required.

On ingestion:

Summon medical aid without delay. Do not induce vomiting due to aspiration hazard. Rinse mouth immediately with water. Keep at rest.

Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Indication of any immediate medical attention and special treatment needed

Treatment: Symptomatic treatment (decontamination, vital functions).

Antidote: No known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:

carbon dioxide, alcohol-resistant foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:

water jet

Special hazards arising from the substance or mixture

nitrogen oxides

Fire will produce dense black smoke. Inhalation of dangerous decomposition products may cause serious damage to health.

Advice for fire-fighters

Special protective equipment:

Appropriate breathing apparatus may be required.

BASF Safety data sheet according to UN GHS 4th rev.

Date / Revised: 14.10.2020

Version: 2.3

Product: **N75-021 Hardener 2,5L**

(ID no. 50655498/SDS_GEN_00/EN)

Date of print 05.11.2020

Further information:

Cool closed containers in the vicinity of the source of fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Avoid breathing vapours. Ensure adequate ventilation. Advice on product handling can be found in sections 7 and 8 of this safety data sheet. Keep away from sources of ignition.

Environmental precautions

Do not allow to enter drains or waterways. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency. Do not discharge into the subsoil/soil.

Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth. Place in a suitable container. The contaminated area should be cleaned up immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises (by volume): ethanol or isopropyl alcohol (50 parts); water (45 parts); concentrated ammonia solution (5 parts). A non-flammable alternative is: sodium carbonate (5 parts); water (95 parts). Add the same decontaminant to the remnants and let stand for several days until no further reaction in non-sealed container. Once this stage is reached, close container and dispose according to the waste regulations (see section 13). Ensure adequate ventilation.

7. Handling and Storage

Precautions for safe handling

Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. Care should be taken when reopening partly used containers (pressurization!). Avoid inhalation of vapour and spray mist. The workplace should be equipped with an emergency shower and eye-rinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapours are heavier than air and spread along floors. Vapour forms explosive mixtures with air. The relevant fire protection measures should be noted. Use explosion-proof equipment.

Conditions for safe storage, including any incompatibilities

Keep away from strongly acid and strongly alkaline materials, from oxidizing agents, amines, alcohols and water.

Suitable materials for containers: Carbon steel (Iron), tinned carbon steel (Tinplate)

Further information on storage conditions: Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Precautions should be taken to minimise exposure to atmospheric humidity or water: carbon dioxide will be formed which in closed containers can result in pressurisation. Always keep in containers of same material as the original one. Observe label precautions.

Storage stability:

Storage temperature: 5,00 - 35,00 °C

Specific end use(s)

Please refer to the technical leaflet for further information.

8. Exposure Controls/Personal Protection**Control parameters**Components with occupational exposure limits

100-41-4: Ethylbenzene

108-10-1: 4-Methylpentan-2-one

112-07-2: 2-Butoxyethyl acetate

123-86-4: n-Butyl acetate

1330-20-7: Xylene

Exposure controlsPersonal protective equipment

Respiratory protection:

full face mask with AB2P3 class combination filter When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators. In situations where dust may occur use appropriate certified respirators. Use A1P2 breathing-protection half mask in case of contact with aerosols.

Hand protection:

Further information on penetration time is available from the manufacturer of the glove.

Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components.

The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

Follow manufacturer's advice on use, storage, maintenance and replacement of gloves.

BASF Safety data sheet according to UN GHS 4th rev.

Date / Revised: 14.10.2020

Version: 2.3

Product: **N75-021 Hardener 2,5L**

(ID no. 50655498/SDS_GEN_00/EN)

Date of print 05.11.2020

The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream).

Wear protective gloves. Any chemical protection glove certified according to EN 374 is suitable: e.g. nitrile gloves - material thickness: 1,25 mm

Eye protection:

Eye protection not required., Required when there is a risk of eye contact.

Body protection:

chemical-resistant disposable coveralls, Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

General safety and hygiene measures

Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible.

Under cool dry conditions, it is possible for the isocyanate to remain unreacted in the paint film for up to 30 hours after application. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. This can be achieved by the use of local exhaust ventilation and good general extraction. Respiratory protective equipment should be worn by spray booth operatives. Ensure adequate ventilation. Remove contaminated clothing immediately and dispose of safely. Hands and/or face should be washed before breaks and at the end of the shift. Keep separated from food stuffs and feed stocks.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Form:	liquid	
Colour:	colourless	
Odour:	specific	
pH value:	not applicable	
Melting point:	not determined	
onset of boiling:	114,00 °C	
Flash point:	44 °C	
Flammability:	Flammable liquid and vapour.	
Lower explosion limit:	36 g/m ³	
Ignition temperature:	> 200,00 °C	
Vapour pressure:	21,50 hPa (20 °C)	(calculated)
	(50 °C)	
Density:	not determined 0,987 g/cm ³ (20 °C)	
Viscosity, kinematic:	6,0 mm ² /s (20 °C)	

BASF Safety data sheet according to UN GHS 4th rev.

Date / Revised: 14.10.2020

Version: 2.3

Product: **N75-021 Hardener 2,5L**

(ID no. 50655498/SDS_GEN_00/EN)

Date of print 05.11.2020

(40 °C)
 not determined
 Explosion hazard: not explosive
 Fire promoting properties: not fire-propagating

Other information

Burning rate: The material doesn't meet the criteria (UN Test N.1 (ready specified in paragraph 33.2.1.4.4 of combustible solids))
 UN manual of tests and criteria.
 Self heating ability: It is not a substance capable of spontaneous heating.
 Miscibility with water: immiscible
 Flow time: < 30 s (DIN EN ISO 2431; 3 mm)

10. Stability and Reactivity**Reactivity**

No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

Vapours may form ignitable mixture with air.

Conditions to avoid

Avoid direct contact with water. Avoid direct sunlight. Avoid all sources of ignition: heat, sparks, open flame.

Incompatible materials

Substances to avoid:

Keep away from oxidising agents, strongly alkaline and strongly acidic materials, amines, alcohols and water. Uncontrolled exothermic reactions occur with amines and alcohols. The product reacts with water resulting in evolution of carbon dioxide. In closed containers, pressure build up could result in distortion, blowing and in extreme cases bursting of the container.

Hazardous decomposition products

:

When exposed to high temperatures hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide, oxides of nitrogen, hydrogen cyanide, monomeric isocyanates may be produced., No hazardous decomposition products if stored and handled as prescribed/indicated.

11. Toxicological Information

Information on toxicological effects

Acute toxicity

Assessment of acute toxicity:

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated and prolonged exposure to solvents at levels significantly above OELs may lead to the development of long-lasting central nervous system disorders such as chronic toxic encephalopathy, signs of toxicity include changes in behaviour and memory. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Virtually nontoxic by inhalation. Of low toxicity after single ingestion.

Information on: Benzoic acid

Experimental/calculated data:

LD50 rat (oral): 2.565 mg/kg (Directive 84/449/EEC, B.1)

Information on: Ethylbenzene

Experimental/calculated data:

LD50 rat (oral): 3.500 mg/kg

Literature data.

Information on: 2-Butoxyethyl acetate

Experimental/calculated data:

LD50 rat (oral): approx. 1.880 mg/kg (OECD Guideline 401)

Information on: Ethyl 3-ethoxypropionate

Experimental/calculated data:

LD50 rat (oral): approx. 5.000 mg/kg (OECD Guideline 401)

Information on: Xylene

Experimental/calculated data:

LD50 rat (oral): 3.523 mg/kg (similar to OECD guideline 401)

Information on: Ethylbenzene

Experimental/calculated data:

LD50 rabbit (dermal): 15.354 mg/kg

Literature data.

BASF Safety data sheet according to UN GHS 4th rev.

Date / Revised: 14.10.2020

Version: 2.3

Product: **N75-021 Hardener 2,5L**

(ID no. 50655498/SDS_GEN_00/EN)

Date of print 05.11.2020

Information on: 2-Butoxyethyl acetate

Experimental/calculated data:

LD50 rabbit (dermal): approx. 1.500 mg/kg

Irritation

Assessment of irritating effects:

The liquid splashed in the eyes may cause irritation and reversible damage. Eye contact causes irritation. Skin contact causes slight irritation.

Respiratory/Skin sensitization

Assessment of sensitization:

Sensitization after skin contact possible.

Germ cell mutagenicity

Assessment of mutagenicity:

Based on available Data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity:

Based on available Data, the classification criteria are not met.

Reproductive toxicity

Assessment of reproduction toxicity:

Based on available Data, the classification criteria are not met.

Developmental toxicity

Assessment of teratogenicity:

Based on available Data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Assessment of STOT single:

Causes temporary irritation of the respiratory tract. Possible narcotic effects (drowsiness or dizziness).

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Repeated exposure may affect certain organs.

Aspiration hazard

No aspiration hazard expected.

Other relevant toxicity information

Based on the properties of the isocyanate components and considering toxicological data on similar product, this product may cause acute irritation and/or sensitization of the respiratory system leading to an asthmatic condition, wheeziness and tightness of the chest. Sensitized persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the occupational exposure limit. Repeated inhalation may lead to a permanent respiratory disability.

12. Ecological Information

Toxicity

Assessment of aquatic toxicity:

Harmful to aquatic life. There are no test results available for this product. Do not allow to enter drains or waterways.

Persistence and degradability

Assessment biodegradation and elimination (H₂O):

Biological degradability of hazardous substances mentioned in section 3:

Information on: Ethylbenzene

Elimination information:

70 - 80 % TIC of the ThIC (28 d) (ISO 14593) (aerobic, activated sludge) Readily biodegradable (according to OECD criteria).

Information on: 2-Butoxyethyl acetate

Elimination information:

88 % BOD of the ThOD (28 d) (OECD 301F; ISO 9408; 92/69/EEC, C.4-D) (aerobic, activated sludge, domestic)

Information on: n-Butyl acetate

Elimination information:

80 % BOD of the ThOD (5 d) (OECD 301D; EEC 92/69, C.4-E) (aerobic, municipal sewage treatment plant effluent)

Information on: Ethyl 3-ethoxypropionate

Elimination information:

100 % CO₂ formation relative to the theoretical value (28 d) (Directive 84/449/EEC, C.5) (aerobic, activated sludge, domestic, non-adapted) Readily biodegradable.

Information on: Xylene

Elimination information:

87,8 % BOD of the ThOD (28 d) (OECD Guideline 301 F) (aerobic, activated sludge, domestic, non-adapted)

BASF Safety data sheet according to UN GHS 4th rev.

Date / Revised: 14.10.2020

Version: 2.3

Product: **N75-021 Hardener 2,5L**

(ID no. 50655498/SDS_GEN_00/EN)

Date of print 05.11.2020

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Information on: p-Toluenesulphonyl isocyanate

Elimination information:

86 % BOD of the ThOD (28 d) (OECD 301D; EEC 92/69, C.4-E) (aerobic, activated sludge, domestic, non-adapted)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Bioaccumulative potential

Bioaccumulation potential:
No data available.

Mobility in soil

Assessment transport between environmental compartments:
Adsorption in soil: No data available.

13. Disposal Considerations

Waste treatment methods

Observe national and local legal requirements.
Dispose of isocyanate waste in dry containers and never mix together with other wastes (reaction, dangerous pressure build up).

Contaminated packaging:
Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.
Residues in empty containers should be neutralised with decontaminant (see section 6).

14. Transport Information

Land transport

ADR

UN number	UN1866
UN proper shipping name:	RESIN SOLUTION
Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	no
Special precautions for	Tunnel code: D/E

BASF Safety data sheet according to UN GHS 4th rev.

Date / Revised: 14.10.2020

Version: 2.3

Product: **N75-021 Hardener 2,5L**

(ID no. 50655498/SDS_GEN_00/EN)

Date of print 05.11.2020

user:

RID

UN number UN1866
UN proper shipping name: RESIN SOLUTION
Transport hazard class(es): 3
Packing group: III
Environmental hazards: no
Special precautions for
user:

Inland waterway transport

ADN

UN number UN1866
UN proper shipping name: RESIN SOLUTION
Transport hazard class(es): 3
Packing group: III
Environmental hazards: no
Special precautions for
user:

Transport in inland waterway vessel

Not evaluated

Sea transport

IMDG

UN number: UN 1866
UN proper shipping name: RESIN SOLUTION
Transport hazard class(es): 3
Packing group: III
Environmental hazards: no
Marine pollutant: NO
Special precautions for
user:

Air transport

IATA/ICAO

UN number: UN 1866
UN proper shipping name: RESIN SOLUTION
Transport hazard class(es): 3
Packing group: III

BASF Safety data sheet according to UN GHS 4th rev.

Date / Revised: 14.10.2020

Version: 2.3

Product: **N75-021 Hardener 2,5L**

(ID no. 50655498/SDS_GEN_00/EN)

Date of print 05.11.2020

Environmental hazards: No Mark as dangerous for the environment is needed
 Special precautions for user:

Transport in bulk according to Annex II of MARPOL and the IBC Code

Regulation: Not evaluated
 Shipment approved: Not evaluated
 Pollution name: Not evaluated
 Pollution category: Not evaluated
 Ship Type: Not evaluated

15. Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Not applicable

16. Other Information

For multi-pack systems observe material safety data sheets of all components. Restricted to professional users.

Full text of classifications, hazard symbols and hazard statements, if mentioned in section 2 or 3:

Acute Tox.	Acute toxicity
Skin Corr./Irrit.	Skin corrosion/irritation
Eye Dam./Irrit.	Serious eye damage/eye irritation
Skin Sens.	Skin sensitization
STOT SE	Specific target organ toxicity — single exposure
Aquatic Acute	Hazardous to the aquatic environment - acute
Flam. Liq.	Flammable liquids
STOT RE	Specific target organ toxicity — repeated exposure
Asp. Tox.	Aspiration hazard
Aquatic Chronic	Hazardous to the aquatic environment - chronic
Resp. Sens.	Respiratory sensitization
H318	Causes serious eye damage.
H315	Causes skin irritation.
H313	May be harmful in contact with skin.
H303	May be harmful if swallowed.
H372	Causes damage to organs (Lung) through prolonged or repeated exposure (inhalation).
H225	Highly flammable liquid and vapour.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs (Auditory organ) through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
H401	Toxic to aquatic life.

BASF Safety data sheet according to UN GHS 4th rev.

Date / Revised: 14.10.2020

Version: 2.3

Product: **N75-021 Hardener 2,5L**

(ID no. 50655498/SDS_GEN_00/EN)

Date of print 05.11.2020

H319	Causes serious eye irritation.
H305	May be harmful if swallowed and enters airways.
H335	May cause respiratory irritation.
H227	Combustible liquid.
H302 + H312	Harmful if swallowed or in contact with skin
H402	Harmful to aquatic life.
H226	Flammable liquid and vapour.
H336	May cause drowsiness or dizziness.
H330	Fatal if inhaled.
H302	Harmful if swallowed.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H320	Causes eye irritation.
H333	May be harmful if inhaled.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH014	Reacts violently with water.
EUH204	Contains isocyanates. May produce an allergic reaction.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.